

Overview

AMD® Radeon™ R9 350 2GB PCIe x16

Models

AMD® Radeon™ R9 350 2GB PCIe x16

N3R91AA

Introduction

Drive your everyday PC, Web conferencing, and video or photo content to up to four displays from one card with the AMD Radeon™ R9 350 2GB PCIe x16 Card.

Performance and Features

- Conveniently expand your connectivity to HDMI from the DisplayPort connector with an optional adapter.¹
- Experience peak bandwidth support from the full 16-lane PCIe 3.0 bus. Eliminate the need to share PC system memory with 2 GB of dedicated GDDR5 memory.
- Work with your familiar tools with a card that supports OpenGL 4.3 and DirectX 11.1 applications.

¹. Sold separately. See product QuickSpecs.

AMD and Radeon are trademarks of Advanced Micro Devices, Inc.

Compatibility

The AMD® Radeon™ R9 350 2GB PCIe x16 is supported on the following platforms:

HP ProDesk400 G3 MT, HP ProDesk 600 G2 MT, HP EliteDesk 705 G2 MT, HP EliteDesk 800 G2 TWR

Service and Support

The AMD® Radeon™ R9 350 2GB PCIe x16 has a one-year limited warranty or the remainder of the warranty of the HP product in which it is installed. Technical support is available seven days a week, 24 hours a day by phone, as well as online support forums. Parts and labor are available on-site within the next business day. Telephone support is available for parts diagnosis and installation. Certain restrictions and exclusions apply.

Technical Specifications

Memory	2GB 128-bit wide frame buffer operating at 1125MHz.
Controller Clock Speed	AMD® Radeon™ R9 350 GPU operating at 925 MHz
Multidisplay Support	A maximum of 4 displays are supported by the card. A maximum of 2 legacy displays (Native VGA, DVI, or displays connected with passive DisplayPort adapters are considered as legacy)
Graphics /API support	DIRECTX 11.1, Open GL 4.3, Open CL1.2, UVD 3
Shader Model Supported	Shader Model 5.0
Output Connectors	1 x Dual-Link DVI-I, 2x DisplayPort; Includes DVI-I to VGA adapter Display Port outputs are multi-mode capable, support Audio, HBR2 and MST

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

* >60 refresh rates only for analog (VGA) signaling

Resolution	Refresh Rate*	(DVI-VGA adapter) VGA	DVI-D	DisplayPort	Standard
640 x 480	60, 75, 85	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	X	VESA DMT, 1.92M3

Technical Specifications

1920 x 1440	60, 75, 85	X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	X	CVT 3.15M3
2560 x 1440	59.951		X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB		X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60		X	X	VESA (SMPTE 274M)
1920 x 1080	50		X	X	SMPTE 274M
1920 x 1080	30		X	X	SMPTE 274M
1920 x 1080	24		X	X	SMPTE 274M
1280 x 720	60		X	X	VESA (CEA-770.3)
1280 x 720	50		X	X	SMPTE 296M
720 x 480	60		X	X	MHL (CEA-770.2)

Agency Approvals

BSMI, CE, ACA, ICES/CISPR, KC, UL, VCCI

Available Graphics Drivers Power Consumption

Microsoft Windows 7x32, 7x64, 8.1x64, 10x64
58W Max average

Kit Contents

AMD® Radeon™ R9 350 2GB PCIe x16 card, DVI-I to VGA adapter are graphics card and documentation

Technical Specifications

© Copyright 2015 Hewlett-Packard Development Company, L.P. All rights reserved.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

AMD and Radeon are trademarks of Advanced Micro Devices, Inc.