



IRONWOLF PRO

NAS



3.5 HDD DATA SHEET

The Power of Agility for Creative Pro and SME NAS Enclosures



IronWolf™ Pro is designed for everything business NAS. Get used to tough, ready and scalable 24x7 performance that can handle multi-drive environments with a wide range of capacities.



Best-Fit Applications

- 1- to 16-bay business network attached storage (NAS)
- Backup, archiving and disaster recovery
- On-premise private cloud
- Virtual storage



Key Advantages

Optimized for NAS with AgileArray.™ AgileArray is built for dual-plane balancing and RAID optimization in multi-bay environments with the most advanced power management possible.

High performance means reduced lag times or downtime for users during high traffic time for the NAS. Seagate leads the competition with the highest performance in NAS-class drives.¹

Seagate® Rescue Data Recovery.² IronWolf Pro comes with extra peace of mind for any mechanical, accidental or natural disaster. With a 90% success rate of in-house recovery, Seagate has your back with a Rescue Data Recovery plan.

Rotational Vibration (RV) mitigation. IronWolf Pro comes standard with RV sensors to maintain high performance in multi-bay NAS enclosures.

Range of capacities up to 10TB. More capacity options mean more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

Get ahead with more cache. IronWolf provides high-cache options allowing your NAS to serve data faster.

Do more with multi-user technology. Enables user workload rate of 300TB/year. Multiple users can confidently upload and download data to the NAS server, knowing it can handle the workload, whether you're a creative professional or small business.

Designed for always on, always accessible 24x7 performance. Access your data on your NAS any time, remotely or on site.

1.2M hours MTBF, 5-year limited warranty represents an improved total cost of ownership (TCO) with reduced maintenance costs.



IRONWOLF PRO

NAS



Specifications	10TB ^{1,2}	8TB ^{1,2}	6TB ^{1,2}	4TB ^{1,2}	2TB ¹
Standard Model Number	ST10000NE0004	ST8000NE0021	ST6000NE0021	ST4000NE0025 ³	ST2000NE0025 ³
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features					
Drive Bays Supported	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays
Multi-User Technology (TB/yr)	300	300	300	300	300
Rotational Vibration (RV) Sensors	Yes	Yes	Yes	Yes	Yes
Hot-Plug Support ⁴	Yes	Yes	Yes	Yes	Yes
Cache (MB)	256MB	256MB	256MB	128MB	128MB
Reliability/Data Integrity					
Mean Time Between Failures (MTBF) (hours)	1.2M	1.2M	1.2M	1.2M	1.2M
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%	0.73%
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours (per year)	8760	8760	8760	8760	8760
Sector Size (Bytes per Logical Sector)	512E	512E	512E	512E	512
Rescue Services ⁵	Yes	Yes	Yes	Yes	Yes
Limited Warranty (years)	5	5	5	5	5
Performance					
Spindle Speed (RPM)	7200	7200	7200	7200	7200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max Sustained Transfer Rate OD (MB/s)	214	214	214	214	195
Average Latency (ms)	4.16	4.16	4.16	4.16	4.16
Interface Ports	Single	Single	Single	Single	Single
Rotational Vibration @ 10-1500 Hz (rad/s ²)	12.5	12.5	12.5	12.5	12.5
Power Consumption					
Startup Current, Typical (12V, A)	2.0	2.0	2.0	2.0	2.0
Idle Power, Average (W)	4.4	7.6	7.6	6.0	4.5
Average Operating Power (W)	6.8	9.0	9.0	6.7	7.5
Standby Mode, Typical (W)	0.8	0.6	0.6	0.6	0.8
Sleep Mode, Typical (W)	0.8	0.6	0.6	0.6	0.8
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V
Environmental					
Temperature (°C)					
Operating (ambient, min)	5	5	5	5	5
Operating (drive case, max)	60	60	60	60	60
Nonoperating (ambient, min)	-40	-40	-40	-40	-40
Nonoperating (ambient, max)	70	70	70	70	70
Vibration, Nonoperating: 10Hz to 500Hz (Grms)	2.27	5	5	5	5
Shock, Operating, 2ms (Read/Write) (Gs)	70/40	70/40	70/40	70/40	70/40
Shock, Nonoperating, 1ms and 2ms (Gs)	250	250	250	300	300
Physical					
Height (mm/in)	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028
Width (mm/in, max)	101.85/4.01	101.85/4.01	101.85/4.01	101.85/4.01	101.85/4.01
Depth (mm/in, max)	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787
Weight (g/lb, typical)	650/1.433	780/1.72	780/1.72	680/1.50	550/1.21

1 One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

2 Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

3 Coming soon. For immediate needs, please see Enterprise NAS HDD.

4 Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.

5 Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details. Register an IronWolf Pro drive to activate your 2-year Rescue plan at seagate.com/register.

seagate.com



AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2016 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1914.1-1611US, November 2016